





Specifications

Width: 55'

Abrasion: 1,500,000 Double Rubs

Finish: Endurepel Armour - Stain & Soil Resistant, Anti-Bacterial

Ecofiendly: Phtalate & FR Additive Free

Breaking: Passes ASTM D751-06: Procedure A, CFFA 17-2013 - Weft 94 x Warp 101 LBF

Cold Crack: Product Cold Crack is Equal to or Greater Than -55°C (-67°F)

Crocking: AATCC 8: Dry = Class 5, AATCC 8: Wet = Class 5 **Elongation:** Passes ASTM D751 - Weft 116% x Warp 64%

Features: Passes AATCC 107-203 Colourfastness to Bleach - Class 5.0, Passes AATCC 147-2011 - Anti-Bacterial, Passes ASTM G21-13-Anti-Fungal, Passes

ASTM D751-06 Coating Adhesion - Weft 4.4 x Warp 5.3 LBS, Passes ASTM E 1428-15A Pink Stain Resistance Fire Retardancy: CALTB117-2013, IMO FTP Code 2010 - Part 8, MVSS302, NFPA 260 Class 1, UFAC Class 1

Mildew Resistance: Mildew Resistant

Seam Slippage: Passes ASTM D751 - Weft 64 x Warp 67 LBS
Tear Strength: Passes ASTM D2261 - Weft 13 x Warp 10 LBS, Passes ASTM D751 - Weft 12 x Warp 10 LBS

Tensile Strength: Passes ASTM D751 - Weft 94 x Warp 101 LBS

UV Resistance: Colourfastness to Light AATCC 16.3 - Grade 4 (1500 Hours)

Weight: 736 Grams per Square Metre, 33.17 Ounces per Linear Yard, 21.71 Ounces per Square Yard Cleaning Code: W - Clean Fabrics with Water-Based Cleaning Agents or Water Based Foam

Approved Cleaners: Cleanable with Virox 5, Oxivir Plus, Oxivir TB, Oxivir TB Wipes, Accel Five TB, Accel PREVention, Accel PREVention Wipes, Oasis 146, Bleach







Specifications

Width: 55'

Abrasion: 1,500,000 Double Rubs

Finish: Endurepel Armour - Stain & Soil Resistant, Anti-Bacterial

Ecofiendly: Phtalate & FR Additive Free

Breaking: Passes ASTM D751-06: Procedure A, CFFA 17-2013 - Weft 94 x Warp 101 LBF

Cold Crack: Product Cold Crack is Equal to or Greater Than -55°C (-67°F)

Crocking: AATCC 8: Dry = Class 5, AATCC 8: Wet = Class 5 **Elongation:** Passes ASTM D751 - Weft 116% x Warp 64%

Features: Passes AATCC 107-203 Colourfastness to Bleach - Class 5.0, Passes AATCC 147-2011 - Anti-Bacterial, Passes ASTM G21-13-Anti-Fungal, Passes

ASTM D751-06 Coating Adhesion - Weft 4.4 x Warp 5.3 LBS, Passes ASTM E 1428-15A Pink Stain Resistance Fire Retardancy: CALTB117-2013, IMO FTP Code 2010 - Part 8, MVSS302, NFPA 260 Class 1, UFAC Class 1

Mildew Resistance: Mildew Resistant

Seam Slippage: Passes ASTM D751 - Weft 64 x Warp 67 LBS
Tear Strength: Passes ASTM D2261 - Weft 13 x Warp 10 LBS, Passes ASTM D751 - Weft 12 x Warp 10 LBS

Tensile Strength: Passes ASTM D751 - Weft 94 x Warp 101 LBS

UV Resistance: Colourfastness to Light AATCC 16.3 - Grade 4 (1500 Hours)

Weight: 736 Grams per Square Metre, 33.17 Ounces per Linear Yard, 21.71 Ounces per Square Yard Cleaning Code: W - Clean Fabrics with Water-Based Cleaning Agents or Water Based Foam

Approved Cleaners: Cleanable with Virox 5, Oxivir Plus, Oxivir TB, Oxivir TB Wipes, Accel Five TB, Accel PREVention, Accel PREVention Wipes, Oasis 146, Bleach







Specifications

Width: 55"

Abrasion: 1,500,000 Double Rubs

Finish: Endurepel Armour - Stain & Soil Resistant, Anti-Bacterial

Ecofiendly: Phtalate & FR Additive Free

Breaking: Passes ASTM D751-06: Procedure A, CFFA 17-2013 - Weft 94 x Warp 101 LBF

Cold Crack: Product Cold Crack is Equal to or Greater Than -55°C (-67°F)

Crocking: AATCC 8: Dry = Class 5, AATCC 8: Wet = Class 5 **Elongation:** Passes ASTM D751 - Weft 116% x Warp 64%

Features: Passes AATCC 107-203 Colourfastness to Bleach - Class 5.0, Passes AATCC 147-2011 - Anti-Bacterial, Passes ASTM G21-13-Anti-Fungal, Passes

ASTM D751-06 Coating Adhesion - Weft 4.4 x Warp 5.3 LBS, Passes ASTM E 1428-15A Pink Stain Resistance **Fire Retardancy:** CALTB117-2013, IMO FTP Code 2010 - Part 8, MVSS302, NFPA 260 Class 1, UFAC Class 1

Mildew Resistance: Mildew Resistant

Seam Slippage: Passes ASTM D751 - Weft 64 x Warp 67 LBS

Tear Strength: Passes ASTM D2261 - Weft 13 x Warp 10 LBS, Passes ASTM D751 - Weft 12 x Warp 10 LBS

Tensile Strength: Passes ASTM D751 - Weft 94 x Warp 101 LBS

Thickness: 1.10mm

UV Resistance: Colourfastness to Light AATCC 16.3 - Grade 4 (1500 Hours)

Weight: 736 Grams per Square Metre, 33.17 Ounces per Linear Yard, 21.71 Ounces per Square Yard **Cleaning Code:** W - Clean Fabrics with Water-Based Cleaning Agents or Water Based Foam

Approved Cleaners: Cleanable with Virox 5, Oxivir Plus, Oxivir TB, Oxivir TB Wipes, Accel Five TB, Accel PREVention, Accel PREVention Wipes, Oasis 146, Bleach







Specifications

Width: 55'

Abrasion: 1,500,000 Double Rubs

Finish: Endurepel Armour - Stain & Soil Resistant, Anti-Bacterial

Ecofiendly: Phtalate & FR Additive Free

Breaking: Passes ASTM D751-06: Procedure A, CFFA 17-2013 - Weft 94 x Warp 101 LBF

Cold Crack: Product Cold Crack is Equal to or Greater Than -55°C (-67°F)

Crocking: AATCC 8: Dry = Class 5, AATCC 8: Wet = Class 5 **Elongation:** Passes ASTM D751 - Weft 116% x Warp 64%

Features: Passes AATCC 107-203 Colourfastness to Bleach - Class 5.0, Passes AATCC 147-2011 - Anti-Bacterial, Passes ASTM G21-13-Anti-Fungal, Passes

ASTM D751-06 Coating Adhesion - Weft 4.4 x Warp 5.3 LBS, Passes ASTM E 1428-15A Pink Stain Resistance Fire Retardancy: CALTB117-2013, IMO FTP Code 2010 - Part 8, MVSS302, NFPA 260 Class 1, UFAC Class 1

Mildew Resistance: Mildew Resistant

Seam Slippage: Passes ASTM D751 - Weft 64 x Warp 67 LBS
Tear Strength: Passes ASTM D2261 - Weft 13 x Warp 10 LBS, Passes ASTM D751 - Weft 12 x Warp 10 LBS

Tensile Strength: Passes ASTM D751 - Weft 94 x Warp 101 LBS

Thickness: 1.10mm

UV Resistance: Colourfastness to Light AATCC 16.3 - Grade 4 (1500 Hours)

Weight: 736 Grams per Square Metre, 33.17 Ounces per Linear Yard, 21.71 Ounces per Square Yard Cleaning Code: W - Clean Fabrics with Water-Based Cleaning Agents or Water Based Foam

Approved Cleaners: Cleanable with Virox 5, Oxivir Plus, Oxivir TB, Oxivir TB Wipes, Accel Five TB, Accel PREVention, Accel PREVention Wipes, Oasis 146, Bleach











Vanilla **White Cap** Wine

Specifications

Width: 55'

Abrasion: 1,500,000 Double Rubs

Finish: Endurepel Armour - Stain & Soil Resistant, Anti-Bacterial

Ecofiendly: Phtalate & FR Additive Free

Breaking: Passes ASTM D751-06: Procedure A, CFFA 17-2013 - Weft 94 x Warp 101 LBF

Cold Crack: Product Cold Crack is Equal to or Greater Than -55°C (-67°F)

Crocking: AATCC 8: Dry = Class 5, AATCC 8: Wet = Class 5 **Elongation:** Passes ASTM D751 - Weft 116% x Warp 64%

Features: Passes AATCC 107-203 Colourfastness to Bleach - Class 5.0, Passes AATCC 147-2011 - Anti-Bacterial, Passes ASTM G21-13-Anti-Fungal, Passes

ASTM D751-06 Coating Adhesion - Weft 4.4 x Warp 5.3 LBS, Passes ASTM E 1428-15A Pink Stain Resistance Fire Retardancy: CALTB117-2013, IMO FTP Code 2010 - Part 8, MVSS302, NFPA 260 Class 1, UFAC Class 1

Mildew Resistance: Mildew Resistant

Seam Slippage: Passes ASTM D751 - Weft 64 x Warp 67 LBS
Tear Strength: Passes ASTM D2261 - Weft 13 x Warp 10 LBS, Passes ASTM D751 - Weft 12 x Warp 10 LBS

Tensile Strength: Passes ASTM D751 - Weft 94 x Warp 101 LBS

UV Resistance: Colourfastness to Light AATCC 16.3 - Grade 4 (1500 Hours)

Weight: 736 Grams per Square Metre, 33.17 Ounces per Linear Yard, 21.71 Ounces per Square Yard Cleaning Code: W - Clean Fabrics with Water-Based Cleaning Agents or Water Based Foam

Approved Cleaners: Cleanable with Virox 5, Oxivir Plus, Oxivir TB, Oxivir TB Wipes, Accel Five TB, Accel PREVention, Accel PREVention Wipes, Oasis 146, Bleach